



Ready Super High Performance




051



081



120



+3°C | -40°C


Models	Tray capacity GN1/1 – EN1	External dimensions (W x D x H mm)	Refrigerant Gas	Positive blast chilling capacity in 90' +90°C > +3°C (Kg)	Negative blast chilling capacity in 240' +90°C > -18°C (Kg)	Electric power (W)	Power absorption (A)	Power supply voltage * (V/Ph/Hz)
RBS-051-SA	5	790 × 820 × 900	R452A	30	20	1046	4,87	220-240/1N-/50
RBS-051-SA-R290	5	790 × 820 × 900	R290	30	20	1405	6,79	220-240/1N-/50
RBS-051-SR	5	790 × 820 × 900	R452a/R448a/R449a	30	20	108	0,51	220-240/1N-/50
RBS-051-SR-CO2	5	790 × 820 × 900	R744 (CO2)	30	20	108	0,51	220-240/1N-/50
RBS-051-SW	5	790 × 820 × 900	R452A	30	20	1038	4,8	220-240/1N-/50
RBS-081-SA	8	790 × 870 × 1460	R452A	40	25	1501	7,53	220-240/1N-/50
RBS-081-SR	8	790 × 870 × 1460	R452a/R448a/R449a	40	25	118	0,56	220-240/1N-/50
RBS-081-SR-CO2	8	790 × 870 × 1460	R744 (CO2)	40	25	119	0,56	220-240/1N-/50
RBS-081-SW	8	790 × 870 × 1460	R452A	40	25	1399	6,77	220-240/1N-/50
RBSR-120-SA	10	850 × 870 × 1860	R452A	65	45	2409	4,73	380-420/3N-/50
RBSR-120-SR	10	850 × 870 × 1860	R452a/R448a/R449a	65	45	199	0,94	380-420/3N-/50
RBSR-120-SW	10	850 × 870 × 1860	R452A	65	45	2297	4,24	380-420/3N-/50

- SA: Air unit
- RA-R290: with ecological gas
- SR: Remote unit (optional)
- SR-CO2: Remote unit set up for CO₂ ecological gas
- SW: Water unit

For maximum overall dimensions and technical specifications, consult the product data sheet.
For condensing units, consult the specific sheet.

* special voltages and frequencies on request


Display 5"




Ready Super High Performance




121



161



122




+3°C | -40°C

Models	Tray capacity GN1/1 - EN1	External dimensions (W x D x H mm)	Refrigerant Gas	Positive blast chilling capacity in 90° +90°C > +3°C (Kg)	Negative blast chilling capacity in 240° +90°C > -18°C (Kg)	Electric power (W)	Power absorption (A)	Power supply voltage * (V/Ph/Hz)
RBS-121-SA	12	790 × 870 × 1810	R452A	65	45	2409	4,73	380-420/3N-/50
RBS-121-SA-R290	12	790 × 870 × 1810	R290	65	45	2505	5,05	380-420/3N-/50
RBS-121-SR	12	790 × 870 × 1810	R452a/R448a/R449a	65	45	199	0,94	380-420/3N-/50
RBS-121-SR-CO2	12	790 × 870 × 1810	R744 (CO2)	65	45	200	0,94	380-420/3N-/50
RBS-121-SW	12	790 × 870 × 1810	R452A	65	45	2297	4,24	380-420/3N-/50
RBS-161-SA	16	790 × 870 × 1960	R452A	80	55	3417	6,54	380-420/3N-/50
RBS-161-SA-R290	16	790 × 870 × 1960	R290	80	55	3196	6,33	380-420/3N-/50
RBS-161-SR	16	790 × 870 × 1960	R452a/R448a/R449a	80	55	280	1,32	380-420/3N-/50
RBS-161-SR-CO2	16	790 × 870 × 1960	R744 (CO2)	80	55	281	1,32	380-420/3N-/50
RBS-161-SW	16	790 × 870 × 1960	R452A	80	55	3305	6,05	380-420/3N-/50
RBS-122-SA	24	1100 × 1080 × 1860	R452A	80	60	3963	8,18	380-420/3N-/50
RBS-122-SR	24	1100 × 1080 × 1860	R452a/R448a/R449a	80	60	273	1,28	380-420/3N-/50
RBS-122-SR-CO2	24	1100 × 1080 × 1860	R744 (CO2)	80	60	273	1,28	380-420/3N-/50
RBS-122-SW	24	1100 × 1080 × 1860	R452A	80	60	3850	7,69	380-420/3N-/50

- SA: Air unit
- RA-R290: with ecological gas
- SR: Remote unit (optional)
- SR-CO2: Remote unit set up for CO₂ ecological gas
- SW: Water unit

For maximum overall dimensions and technical specifications, consult the product data sheet.
For condensing units, consult the specific sheet.

Display 5"




* special voltages and frequencies on request


Ready Regular




O51



O81



120



+3°C | -40°C

Models	Tray capacity GN1/1 - EN1	External dimensions (W x D x H mm)	Refrigerant Gas	Positive blast chilling capacity in 90' +90°C > +3°C (Kg)	Negative blast chilling capacity in 240' +90°C > -18°C (Kg)	Electric power (W)	Power absorption (A)	Power supply voltage * (V/Ph/Hz)
RBS-051-RA	5	790 x 800 x 900	R452A	25	15	1046	4,87	220-240/1N-/50
RBS-051-RR	5	790 x 800 x 900	R452a/R448a/R449a	25	15	108	0,51	220-240/1N-/50
RBS-051-RW	5	790 x 800 x 900	R452A	25	15	1038	4,8	220-240/1N-/50
RBS-081-RA	8	790 x 850 x 1460	R452A	30	20	1501	7,53	220-240/1N-/50
RBS-081-RR	8	790 x 850 x 1460	R452a/R448a/R449a	30	20	118	0,56	220-240/1N-/50
RBS-081-RW	8	790 x 850 x 1460	R452A	30	20	1399	6,77	220-240/1N-/50
RBSR-120-RA	10	850 x 850 x 1860	R452A	55	35	1846	9,24	220-240/1N-/50
RBSR-120-RR	10	850 x 850 x 1860	R452a/R448a/R449a	55	35	199	0,94	220-240/1N-/50
RBSR-120-RW	10	850 x 850 x 1860	R452A	55	35	1744	8,48	220-240/1N-/50

- RA: Air unit
- RR: Remote unit (optional)
- RW: Water unit

Display 5"




For maximum overall dimensions and technical specifications, consult the product data sheet.
For condensing units, consult the specific sheet.

* special voltages and frequencies on request


Ready Regular




121



161



122




+3°C | -40°C

Models	Tray capacity GN1/1 - EN1	External dimensions (W x D x H mm)	Refrigerant Gas	Positive blast chilling capacity in 90° +90°C > +3°C (Kg)	Negative blast chilling capacity in 240° +90°C > -18°C (Kg)	Electric power (W)	Power absorption (A)	Power supply voltage * (V/Ph/Hz)
RBS-121-RA	12	790 × 850 × 1810	R452A	55	35	1846	9,24	220-240/1N-/50
RBS-121-RR	12	790 × 850 × 1810	R452a/R448a/R449a	55	35	199	0,94	220-240/1N-/50
RBS-121-RW	12	790 × 850 × 1810	R452A	55	35	1744	8,48	220-240/1N-/50
RBS-161-RA	16	790 × 850 × 1960	R452A	75	50	2490	5,11	380-420/3N-/50
RBS-161-RR	16	790 × 850 × 1960	R452a/R448a/R449a	75	50	280	1,32	380-420/3N-/50
RBS-161-RW	16	790 × 850 × 1960	R452A	75	50	2378	4,62	380-420/3N-/50
RBS-122-RA	24	1100 × 1060 × 1860	R452A	75	50	3410	6,5	380-420/3N-/50
RBS-122-RR	24	1100 × 1060 × 1860	R452a/R448a/R449a	75	50	273	1,28	380-420/3N-/50
RBS-122-RW	24	1100 × 1060 × 1860	R452A	75	50	3297	6,01	380-420/3N-/50

- RA: Air unit
- RR: Remote unit (optional)
- RW: Water unit

Display 5"



For maximum overall dimensions and technical specifications, consult the product data sheet.
For condensing units, consult the specific sheet.

* special voltages and frequencies on request