

# Ready Cells



1 Trolley



2 Trolleys



3 Trolleys




4 Trolleys

+3°C | -40°C

Models	Trolleys 20 Pans EN1-GN1/1	Trolleys 20 Pans EN2-GN2/1	Doors	External dimensions (W x D x H mm)	Internal dimensions (W x D x H mm)	Positive blast chilling capacity in 90' +90°C > +3°C (Kg)	Negative blast chilling capacity in 240' +90°C > -18°C (Kg)	Electric power (W)	Power absorption (A)	Power supply voltage* (V/Ph/Hz)
RCSG-201-R-RIF	1		1	1300 x 1330 x 2100	700 x 950 x 1820	120	80	638	2,87	380-420/3N-/50
RCSG-201-R-RTF	1		2	1300 x 1400 x 2100	700 x 1020 x 1820	120	80	738	3,31	380-420/3N-/50
RCSG-202-R-RIF	1	1	1	1500 x 1530 x 2100	880 x 1150 x 1820	150	100	638	2,87	380-420/3N-/50
RCSG-202-R-RTF	1	1	2	1500 x 1600 x 2100	880 x 1220 x 1820	150	100	738	3,31	380-420/3N-/50
RCSG-401-R-RTF	2		2	1300 x 2300 x 2100	700 x 1920 x 1820	240	160	1276	3,56	380-420/3N-/50
RCSG-402-R-RTF	2	2	2	1500 x 2700 x 2100	880 x 2320 x 1820	300	200	1276	3,56	380-420/3N-/50
RCSG-601-R-RTF	3		2	1300 x 3200 x 2100	700 x 2820 x 1820	360	240	1814	3,82	380-420/3N-/50
RCSG-602-R-RTF	3	3	2	1500 x 3800 x 2100	880 x 3420 x 1820	450	300	1814	3,82	380-420/3N-/50
RCSG-801-R-RTF	4		2	1300 x 4100 x 2100	700 x 3720 x 1820	480	320	2232	5,74	380-420/3N-/50
RCSG-802-R-RTF	4	4	2	1500 x 4900 x 2100	880 x 4520 x 1820	600	400	2232	5,74	380-420/3N-/50

• Arrangement for R452a/R448a/R449a refrigerant gas



RIF: 1 door RTF: 2 sliding doors on both sides

• R-REF: regular roll-in with floor

• R-RTF: regular roll-through with floor

For maximum overall dimensions and technical specifications, consult the product data sheet.  
For condensing units, consult the specific sheet.

\* special voltages and frequencies on request

# Ready Cells

On feet



1 oven trolley EN1-GN1/1



1 oven trolley EN2-GN2/1

**+3°C | -40°C**

Models	Trolleys 20 Pans EN1-GN1/1	Trolleys 20 Pans EN2-GN2/1	Doors	External dimensions (W x D x H mm)	Internal dimensions (W x D x H mm)	Positive blast chilling capacity in 90' +90°C > +3°C (Kg)	Negative blast chilling capacity in 240' +90°C > -18°C (Kg)	Electric power (W)	Power absorption (A)	Power supply voltage * (V/Ph/Hz)
RCSG-201-R-OTR	1		1	1300 x 1305 x 2203	740 x 940 x 1700	100	70	638	2,87	380-420/3N-/50
RCSG-201-R-OTR-L	1		1	1300 x 1305 x 2203	740 x 940 x 1700	100	70	638	2,87	380-420/3N-/50
RCSG-202-R-OTR		1	1	1500 x 1505 x 2203	940 x 1140 x 1700	130	90	638	2,87	380-420/3N-/50
RCSG-202-R-OTR-L		1	1	1500 x 1505 x 2203	940 x 1140 x 1700	130	90	638	2,87	380-420/3N-/50

- Arrangement for R452a/R448a/R449a refrigerant gas

- R-OTR: regular oven trolley for ICP trolley

- R-OTR-L: regular oven trolley for Lainox trolley

For maximum overall dimensions and technical specifications, consult the product data sheet.  
For condensing units, consult the specific sheet.

\* special voltages and frequencies on request