

Submarine Cells Gastronomy



1 Trolley



2 Trolleys



3 Trolleys




4 Trolleys

+85°C | -40°C

Models	Trolleys 20 Pans EN1-GN1/1	Trolleys 20 Pans EN2-GN2/1	Doors	External dimensions (W x D x H mm)	Internal dimensions (W x D x H mm)	Positive blast chilling capacity in 90' +90°C > +3°C (Kg)	Negative blast chilling capacity in 240' +90°C > -18°C (Kg)	Electric power (W)	Power absorption (A)	Power supply voltage * (V/Ph/Hz)
SCMG-201-S-RIF	1		1	1300 x 1330 x 2200	700 x 950 x 1820	150	100	6218	10,78	380-420/3N-/50
SCMG-201-S-RTF	1		2	1300 x 1400 x 2200	700 x 880 x 1820	150	100	6318	11,22	380-420/3N-/50
SCMG-202-S-RIF	1	1	1	1500 x 1530 x 2200	880 x 1150 x 1820	180	120	6218	10,78	380-420/3N-/50
SCMG-202-S-RTF	1	1	2	1500 x 1600 x 2200	880 x 1220 x 1820	180	120	6318	11,22	380-420/3N-/50
SCMG-401-S-RTF	2		2	1300 x 2300 x 2200	700 x 1920 x 1820	300	200	12436	21,56	380-420/3N-/50
SCMG-402-S-RTF	2	2	2	1500 x 2700 x 2200	880 x 2320 x 1820	360	240	12436	21,56	380-420/3N-/50
SCMG-601-S-RTF	3		2	1300 x 3200 x 2200	700 x 2820 x 1820	450	300	18554	31,92	380-420/3N-/50
SCMG-602-S-RTF	3	3	2	1500 x 3800 x 2200	880 x 3420 x 1820	540	360	18554	31,92	380-420/3N-/50
SCMG-801-S-RTF	4		2	1300 x 4100 x 2200	700 x 3720 x 1820	600	400	24672	42,26	380-420/3N-/50
SCMG-802-S-RTF	4	4	2	1500 x 4900 x 2200	880 x 4520 x 1820	720	480	24672	42,26	380-420/3N-/50

• Arrangement for R452a/R448a/R449a refrigerant gas



RIF: 1 door RTF: 2 sliding doors on both sides

- S-RIF: Standard roll-in with floor
- S-RTF: Standard roll-through with floor

For maximum overall dimensions and technical specifications, consult the product data sheet.
For condensing units, consult the specific sheet.

* special voltages and frequencies on request

Submarine Cells Pastry



1 Trolley



2 Trolleys



3 Trolleys




4 Trolleys

+45°C | -40°C

Models	Trolleys 20 Pans EN1-GN1/1	Trolleys 20 Pans EN2-GN2/1	Doors	External dimensions (W x D x H mm)	Internal dimensions (W x D x H mm)	Positive blast chilling capacity in 90' +90°C > +3°C (Kg)	Negative blast chilling capacity in 240' +90°C > -18°C (Kg)	Electric power (W)	Power absorption (A)	Power supply voltage * (V/Ph/Hz)
SCBP-201-H-RIF	1		1	1500 x 1330 x 2400	700 x 880 x 2020	220	150	6278	10,48	380-420/3N-/50
SCBP-201-H-RTF	1		2	1500 x 1330 x 2400	700 x 880 x 2020	220	150	6378	10,92	380-420/3N-/50
SCBP-202-H-RIF	2	1	1	1700 x 1530 x 2400	900 x 1080 x 2020	280	220	6968	12,28	380-420/3N-/50
SCBP-202-H-RTF	2	1	2	1700 x 1530 x 2400	900 x 1080 x 2020	280	220	7068	12,72	380-420/3N-/50
SCBP-401-H-RTF	2		2	1500 x 2300 x 2400	700 x 1780 x 2020	440	300	12556	20,96	380-420/3N-/50
SCBP-402-H-RTF	4	2	2	1700 x 2700 x 2400	900 x 2180 x 2020	560	440	13936	24,56	380-420/3N-/50
SCBP-601-H-RTF	3		2	1500 x 3200 x 2400	700 x 2680 x 2020	660	450	18734	31,02	380-420/3N-/50
SCBP-602-H-RTF	6	3	2	1700 x 3800 x 2400	900 x 3280 x 2020	840	660	20804	36,42	380-420/3N-/50
SCBP-801-H-RTF	4		2	1500 x 4100 x 2400	700 x 3580 x 2020	880	600	24912	41,06	380-420/3N-/50
SCBP-802-H-RTF	8	4	2	1700 x 4900 x 2400	900 x 4380 x 2020	1120	880	27672	48,26	380-420/3N-/50

• Arrangement for R452a/R448a/R449a refrigerant gas



RIF: 1 door RTF: 2 sliding doors on both sides

- H-RIF: High power roll-in with floor
- H-RTF: High power roll-through with floor

For maximum overall dimensions and technical specifications, consult the product data sheet.
For condensing units, consult the specific sheet.

* special voltages and frequencies on request

Submarine Cells

On Feet



1/1 GN



2/1 GN

+85°C | -40°C

Models	Trolleys 20 Pans EN1-GN1/1	Trolleys 20 Pans EN2-GN2/1	Doors	External dimensions (W x D x H mm)	Internal dimensions (W x D x H mm)	Positive blast chilling capacity in 90' +90°C > +3°C (Kg)	Negative blast chilling capacity in 240' +90°C > -18°C (Kg)	Electric power (W)	Power absorption (A)	Power supply voltage* (V/Ph/Hz)
SCMR-201-H-OTR	1		1	1500 x 1330 x 2330	700 x 880 x 1700	150	100	5348	8,56	380-420/3N-/50
SCMR-201-H-OTR-L	1		1	1500 x 1330 x 2330	700 x 880 x 1700	150	100	5348	8,56	380-420/3N-/50
SCMR-202-H-OTR		1	1	1700 x 1530 x 2330	900 x 1080 x 1700	200	140	5348	8,56	380-420/3N-/50
SCMR-202-H-OTR-L		1	1	1700 x 1530 x 2330	900 x 1080 x 1700	200	140	5348	8,56	380-420/3N-/50

• Arrangement for R452a/R448a/R449a refrigerant gas

- H-OTR: High power oven trolley for ICP trolley
- H-OTR-L: High power oven trolley for Lainox trolley

Submarine Cells

On Feet, CO₂



+3°C | -40°C

Models	Trolleys 20 Pans EN1-GN1/1	Trolleys 20 Pans EN2-GN2/1	Doors	External dimensions (W x D x H mm)	Internal dimensions (W x D x H mm)	Positive blast chilling capacity in 90' +90°C > +3°C (Kg)	Negative blast chilling capacity in 240' +90°C > -18°C (Kg)	Electric power (W)	Power absorption (A)	Power supply voltage* (V/Ph/Hz)
SCBR-201-H-OTR-CO2	1		1	1500 x 1330 x 2330	700 x 880 x 1700	150	100	848	2,06	380-420/3N-/50
SCBR-201-H-OTR-CO2-L	1		1	1500 x 1330 x 2330	700 x 880 x 1700	150	100	848	2,06	380-420/3N-/50
SCBR-202-H-O -CO2		1	1	1700 x 1530 x 2400	900 x 1080 x 1700	200	140	848	2,06	380-420/3N-/50
SCBR-202-H-OTR-CO2-L		1	1	1700 x 1530 x 2330	900 x 1080 x 1700	200	140	848	2,06	380-420/3N-/50

• Arrangement for R452a/R448a/R449a refrigerant gas

- H-OTR-CO2: High power oven trolley for ICP trolley
- H-OTR-CO2-L: High power oven trolley for Lainox trolley

Submarine Cells CO₂



1 Trolley



2 Trolleys



3 Trolleys




4 Trolleys

+3°C | -40°C

Models	Trolleys 20 Pans EN1-GN1/1	Trolleys 20 Pans EN2-GN2/1	Doors	External dimensions (W x D x H mm)	Internal dimensions (W x D x H mm)	Positive blast chilling capacity in 90' +90°C > +3°C (Kg)	Negative blast chilling capacity in 240' +90°C > -18°C (Kg)	Electric power (W)	Power absorption (A)	Power supply voltage * (V/Ph/Hz)
SCBP-201-H-RIF-CO2	1		1	1500 x 1330 x 2400	700 x 880 x 2020	220	150	1778	3,98	380-420/3N-/50
SCBP-201-H-RTF-CO2	1		2	1500 x 1330 x 2400	700 x 880 x 2020	220	150	1878	4,42	380-420/3N-/50
SCBP-202-H-RTF-CO2	2	1	1	1700 x 1530 x 2400	900 x 1080 x 2020	280	220	2468	5,78	380-420/3N-/50
SCBP-202-H-RTF-CO2	2	1	2	1500 x 1330 x 2330	900 x 1080 x 2020	280	220	2568	6,22	380-420/3N-/50
SCBP-401-H-RTF-CO2	2		2	1500 x 2300 x 2400	700 x 1780 x 2020	440	300	3556	7,97	380-420/3N-/50
SCBP-402-H-RTF-CO2	4	2	2	1700 x 2700 x 2400	900 x 2180 x 2020	560	440	4936	11,57	380-420/3N-/50
SCBP-601-H-RTF-CO2	3		2	1500 x 3200 x 2400	700 x 2680 x 2020	660	450	5234	11,53	380-420/3N-/50
SCBP-602-H-RTF-CO2	6	3	2	1700 x 3800 x 2400	900 x 3280 x 2020	840	660	7304	16,93	380-420/3N-/50
SCBP-801-H-RTF-CO2	4		2	1500 x 4100 x 2400	700 x 3580 x 2020	880	600	6912	15,08	380-420/3N-/50
SCBP-802-H-RTF-CO2	8	4	2	1700 x 4900 x 2400	900 x 4380 x 2020	1120	880	9672	22,28	380-420/3N-/50

• Arrangement for R452a/R448a/R449a refrigerant gas



RIF: 1 door RTF: 2 sliding doors on both sides

- H-RIF: High power roll-in with floor
- H-RTF: High power roll-through with floor

For maximum overall dimensions and technical specifications, consult the product data sheet.
For condensing units, consult the specific sheet.