


Cherry

Genuine freshness

Friulinox






Fresh or frozen

Temperature range -25°C / $+8^{\circ}\text{C}$




Easy to use

Command interface
with capacitive teletermostat



Ideal for any installation

High efficiency tropicalized group
(class "T" 43°C)



High insulation thickness

Less heat loss
for lower energy consumption



Respecting the environment

Climate class 5
R290 ecological refrigerant gas

From the cold specialists comes the new line of **Cherry** cabinets, dedicated to the world of pastry and ice cream, which are **available in different temperatures, according to the products to be stored**, with tray sizes **EN1**, **EN2**, and **ICE**. Thanks to the different technological solutions for temperature and humidity control, they always guarantee perfect product conservation.

Cherry

Genuine freshness



Features

- HACCP alarms indication.
- Control interface with capacitive remote thermostat.
- Monocoque construction.
- Stainless steel interior.
- Scotch Brite satin finish stainless steel exterior.
- Insulation thickness: 80 mm.
- CFC- and HCFC-free high-density PU insulation (42 kg/m³).
- Self-closing doors with 100° opening lock, and magnetic gaskets on all 4 sides.
- Cell with rounded corners for easy cleaning.
- Indirect ventilation thanks to the full-height ducting system for optimal air circulation and uniform temperature distribution.
- Integrated LED lighting on the console.
- Openable stainless steel instrument panel to facilitate periodic maintenance.

- Monobloc ceiling system with evaporator outside the cell to allow use of the entire refrigerated volume.
- Automatic condensate evaporation and defrost device without the use of electricity.
- Tropicalised unit (class <T= 43°C).
- Climate class 5.
- Ecological refrigerant R290
- Full-height ergonomic stainless steel handle.
- Lock.

Standard accessories

- 20 pairs of L-shaped rails.

Accessories

- 2 wheel kit with brake.

Patisserie

Model	Dimensions (L x D x H mm)	Grille capacity	Range Temperature	Refrigerant gas	Power (W)	Absorption (A)	Power supply (V/Ph/Hz) *
CRC11A	780 × 800 × 2090	20 × EN1	-2/+8 °C	R290	208	1,0	220-240/1N-/50
CFC11A	780 × 800 × 2090	20 × EN1	-25/-15 °C	R290	684	3,3	220-240/1N-/50
CRC21A	780 × 1080 × 2090	20 × EN2	-2/+8 °C	R290	295	1,4	220-240/1N-/50
CFC21A	780 × 1080 × 2090	20 × EN2	-25/-15 °C	R290	906	4,4	220-240/1N-/50

* special voltages and frequencies on request

Ice Cream

Model	Dimensions (L x D x H mm)	Capacity of ice cream tubs	Range Temperature	Refrigerant gas	Power (W)	Absorption (A)	Power supply (V/Ph/Hz) *
CGCG1A	780 × 965 × 2090	54 pz 165 × 360 mm H 120mm	-25/-12 °C	R290	906	4,4	220-240/1N-/50

* special voltages and frequencies on request

Cherry

RF54C00009

FRIULINOX - ALI GROUP Srl a Socio Unico
Via Treviso 4 - 33083 Taiedo di Chions (PN) ITALY
Tel. +39 0434 635411 - Fax +39 0434 635414

info@friulinox.com | www.friulinox.com

The data and information may change based on the continual development of products.
See the complete range on: www.friulinox.com

an Ali Group Company



The Spirit of Excellence